

# Kreisregner Messing 3/4" Innengewinde 4,0 mm Typ RC 130 HH (0699008)



# TECHNISCHE DATEN

Typ	RC 130 HH
Werkstoff	Messing
Anschluss	Innengewinde
Düsen	4,0 mm
Capacity 3bar	1,08 m <sup>3</sup> /h
Capacity 4bar	1,22 m <sup>3</sup> /h
Capacity 5bar	1,36 m <sup>3</sup> /h
Maß	3/4"
Radius 3bar	15 m
Radius 4bar	15,2 m
Radius 5bar	15,8 m

Type RC 130 HH																	
4.0mm			4.8mm			4.9mm			4.0mm x 2.4mm			4.4mm x 2.4mm			4.8mm x 3.2mm		
Bar	Q	D	Bar	Q	D	Bar	Q	D	Bar	Q	D	Bar	Q	D	Bar	Q	D
2.5	0.95	26.0	2.5	1.15	27.8	2.5	1.40	30.0	2.5	1.35	26.0	2.5	1.51	27.0	2.5	2.05	30.0
3.5	1.15	27.0	3.5	1.38	28.4	3.5	1.67	30.8	3.5	1.60	27.0	3.5	1.80	28.4	3.5	2.40	30.8
4.5	1.30	27.5	4.5	1.55	29.4	4.5	1.87	31.8	4.5	1.76	27.5	4.5	2.03	29.4	4.5	2.75	31.8

# PRODUKTINFORMATIONEN

Regner mit drehbarer Kunststoffkappe zum Schutz der Feder.  
Besonders als Frostschutzregner geeignet.

**Generiert am: 24.05.2026**

bevo Vertriebs GmbH  
Industriestraße 18  
32602 VLOTHO-EXTER  
Deutschland  
+49 (0) 5228 959 0  
[info@bevo.com](mailto:info@bevo.com)  
<http://www.bevo.com>