

Matarvattentank 3/4" x 1" utvändig gänga 230VAC type Premium (7033731)



TEKNISKA SPECIFIKATIONER

Tank	55 L
Anslutning	utvändig gänga
Max flow	4.8 L/min
Volt	230VAC
Max arbetstryck	4 bar
Typ	Premium
Storlek	3/4" x 1"

PRODUKTINFORMATION

Advantages over conventional separation stations

- Constant watering at maximum pressure
- Pressure increase for irrigation systems on slopes
- Fully automatic through integrated pump control
- Amortisation by reducing the sewage fee (built-in drinking water meter) *
- No noise pollution in the building
- Retrofittable
- No intervention in the drinking water installation necessary
- Outdoor / no risk of flooding for the basement
- Quick and easy installation, even without specialist tradesman possible **
- Maximum comfort and optimal security of supply
- Lockable, to prevent unauthorised access
- For seasonal outdoor use

- Optional extension by e.g. fertiliser admixture

* - Not every water supplier recognises the built-in water meter for billing the sewage fees

** - For the standard-compliant connection via the connection accessory hose, according to DIN EN 1717 and DIN 1988 100, connection must be made with a system separator type BA which can be installed on the tap.

Genererad den: 06/10/2025

Bevo Nordic A/S
Pakhusgården 54
5000 Odense C
Danmark
+45 66 19 25 45
info@bevo.dk
<http://www.bevo.com>