

DAB jet-pump gjutjärn 1" invändig gänga 6bar 5,1A 230VAC grön självsugande med tryckkontroll type JET 102 Control D (7030929)



TEKNISKA SPECIFIKATIONER

Färg	grön
Material	gjutjärn
Pump body	gjutjärn
Material impeller 1	teknopolymer A
Modell	själv sugande med tryckkontroll
Anslutning	invändig gänga
Volt	230VAC
Max temperatur	35 °C
Minste mellantemperatur (kontinuerlig)	0 °C
Tryck	1 "
Max omgivningstemperatur	40 °C
Sug	1 "
Typ	JET 102 Control D
Storlek	1"
Effekt	0.75 kW
MWC	53,8

Ampere	5,1 A
Max flow rate	3.6 m ³ /h
BEP Capacity	2.4
BEP Head	31.8
PORlh	36.5
PORhh	29
PORlq	1.7
PORhq	2.9

DIMENSIONER



Cb-1	144 mm
Cl-1	108 mm
G	111 mm
H	203 mm
H	203 mm
L	414 mm
L	430 mm
Mr	197 mm
O	9 mm

W 178 mm

W-1 178 mm

ØDi-1 1 "

ØDi-2 1 "



PRODUKTINFORMATION

Installation: Horizontal, Fixed. Operating range: from 0.4 to 3.6 m³/h with head up to 53 metres. Suitable for pumping water with low levels of sand impurities. Self priming centrifugal pumps with excellent suction capacity even when air bubbles are present.

Genererad den: 14/03/2026

Bevo Nordic A/S
Pakhusgården 54
5000 Odense C
Danmark
+45 66 19 25 45
info@bevo.dk
<http://www.bevo.com>