

**DAB Dränkbar pump  
teknopolymer 1 1/4" invändig  
gänga 3,4A 230VAC svart/grå  
type DTRON 2 35/90 (7033714)**



# TEKNISKA SPECIFIKATIONER

Färg	svart/grå
Material	teknopolymer
Pump body	teknopolymer
Material impeller 1	teknopolymer
Anslutning	invändig gänga
Volt	230VAC
Max temperatur	50 °C
Minste mellantemperatur (kontinuerlig)	0 °C
Tryck	1 1/4 "
Max omgivningstemperatur	50 °C
Minimum ambient temperature	0 °C
Typ	DTRON 2 35/90
Uteffekt	0,7 Hk
MWC	37 m
Storlek	1 1/4"
Effekt	0.52 kW

Ampere	3,4 A
--------	-------

Max flow rate	6 m <sup>3</sup> /h
---------------	---------------------

BEP Capacity	4
--------------	---

BEP Head	19.8
----------	------

PORlh	0.6
-------	-----

PORhh	37
-------	----

PORlq	0.7
-------	-----

PORhq	6
-------	---

## DIMENSIONER

Db	185 mm
----	--------

H-2	611 mm
-----	--------

ØDi-1	1 1/4 "
-------	---------





# PRODUKTINFORMATION

Installation: Fixed, horizontal or vertical. Submerged or semi-submerged. Maximum immersion depth: 7/12 m Pump can be used with liquids containing solid particles of up to 2 mm in size. Suitable for use in residential building services for pressurisation, rainwater reuse, gardening and irrigation. Integrated debris filter and check valve. Electronic operation allows the pump to start and stop autonomously in line with system requirements and protects against a dry run.

**Genererad den: 28/05/2026**

Bevo Nordic A/S  
Pakhusgården 54  
5000 Odense C  
Danmark  
+45 66 19 25 45  
[info@bevo.dk](mailto:info@bevo.dk)  
<http://www.bevo.com>