

**Tavlit Semi-automatiskt filter
fiberglasförstärkt nylon 2"
utvändig gänga 10bar
120mikron 0,12 mm disk svart
type Adir One-Action Super
(7028549)**



TEKNISKA SPECIFIKATIONER

Färg	svart
Typ	Adir One-Action
Material	fiberglasförstärkt nylon
Material filterelement	disk
Filtrering	120 mikron
Filtrering	120 mesh
Packningsmaterial	EPDM
Anslutning	utvändig gänga
Längd	235 mm
Vikt	8.6 kg
Höjd	645 mm
Tryck	10 bar
Kapacitet	25 m ³ /h
Storlek	2"
Backspolnings flow rate	9,3 m ³ /h
Typ	Super
Filteryta	0.1025 m ²

Filtrering

0,12 mm

PRODUKTINFORMATION

One Action cleaning saves water as the water used for flushing the discs is filtered with an internal screen and put back in the system.

Comes with a standard pressure indicator that shows the user that the filter is dirty and needs flushing (preset value set to 0.5b).

Flushing is performed simply by turning the operation handle $\frac{1}{4}$ of a turn for 20 seconds.

During flushing, the flow to the field is uninterrupted.

Minimum flushing pressure required: 2bar.

Flushing flow rate: 2bar = 9.3m³/h, 3bar = 12m³/h.

When the filter is clean after flushing, the user needs to flush the secondary port by opening the service valve for 10 seconds.

We recommend to install a manual valve (open/close) in the upstream.

Genererad den: 10/03/2026

Bevo Nordic A/S
Pakhusgården 54
5000 Odense C
Danmark
+45 66 19 25 45
info@bevo.dk
<http://www.bevo.com>