

Tavlit Automatisk filterstation fiberglasförstärkt nylon DN110 fläns 10bar 100mikron DN110 disk 9-12VDC latch svart PN10 3 x 2" filter type TAD (7028572)



TEKNISKA SPECIFIKATIONER

Färg svart

Typ TAD

Material fiberglasförstärkt nylon

Material filterelement disk

Filtrering 100 mikron

Filtrering 140 mesh

Packningsmaterial EPDM

Anslutning fläns

Min. temp. 0 °C

Volt 9-12VDC latch

Höjd 1000 mm

Tryck 10 bar

Max temp. 60 °C

Kapacitet 60 m³/h

Modell 3 x 2" filter

Storlek DN110

Längd 1100 mm

DN	110
----	-----

Fläns	PN10
-------	------

Bredd	1100 mm
-------	---------

Filteryta	3.3 m ²
-----------	--------------------

PRODUKTINFORMATION

TAD automatic disc filtration station. When the head loss reaches a preset value of 0.5b-0.7b, the controller starts flushing one filter after the other. Flushing cycle will take from 12 to 30 seconds, depending on the dirt load. During flushing, the flow to the field is uninterrupted. Minimum flushing pressure required: 2.5bar. Flushing flow rate: 9.3m³/h. Components: Talgil controller, Bermad backflush valves and PE manifolds. Configuration: Parallel with downstream (outlet) on the opposite side of the upstream (inlet). For special configurations or components please contact us.

Genererad den: 28/05/2026

Bevo Nordic A/S
Pakhusgården 54
5000 Odense C
Danmark
+45 66 19 25 45
info@bevo.dk
<http://www.bevo.com>